Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/12/2014 : Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : MIGHTY GLASS CLEANER 18 OZ.

Product code : MN103

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Glass Cleaner

1.3. Details of the supplier of the safety data sheet

Mighty Auto Parts 650 Engineering Drive Norcross, Georgia 30092 T 770-448-3900

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280 Muta. 1B H340 Carc. 1A H350 STOT SE 1 H370

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H340 - May cause genetic defects H350 - May cause cancer H370 - Causes damage to organs

Precautionary statements (GHS-US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P307+P311 - If exposed: Call a poison center/doctor

P308+P313 - If exposed or concerned: Get medical advice/attention

P321 - Specific treatment: See section 4.1 on SDS

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

10/12/2014 EN (English US) 1/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
DI - Water	(CAS No) 7789-20-0	85 - 95	Not classified
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Petroleum Gases, Liquefied, Sweetened	(CAS No) 68476-86-8	1 - 5	Flam. Gas 1, H220 Flam. Liq. 1, H224 Muta. 1B, H340 Carc. 1A, H350
2-Butoxyethanol	(CAS No) 111-76-2	<1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Ethanol	(CAS No) 64-17-5	0.7785 - 0.865	Flam. Liq. 2, H225 Carc. 1A, H350
Ammonium Hydroxide, Aqueous Solution, Conc=25%	(CAS No) 1336-21-6	< 1	Skin Corr. 1B, H314 Aquatic Acute 1, H400
2-Aminoethanol	(CAS No) 141-43-5	<= 0.05593	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314
Methyl Isobutyl Ketone	(CAS No) 108-10-1	0.00865 - 0.04325	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation:gas), H331 Eye Irrit. 2A, H319 STOT SE 3, H335
Proprietary Inhibitor Package	(CAS No) Proprietary	<= 0.01974	Not classified
Polyethylene Glycol 200-600	(CAS No) 25322-68-3	<= 0.00144	Not classified
Nonyl Nonoxynol-5	(CAS No) 9014-93-1	<= 0.00096	Not classified

SECTION 4: First aid measures

Description of first aid measures

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice First-aid measures general

(show the label where possible). Call a POISON CENTER or doctor/physician. First-aid measures after inhalation

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by First-aid measures after skin contact

warm water rinse.

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water First-aid measures after eye contact

for several minutes. Obtain medical attention if pain, blinking or redness persist.

Remove to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause genetic defects. Causes damage to organs.

Symptoms/injuries after inhalation : May cause cancer by inhalation.

Symptoms/injuries after skin contact May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin

rash/inflammation.

: May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye Symptoms/injuries after eye contact

tissue. Irritation of the eye tissue. Redness of the eye tissue.

: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways. Symptoms/injuries after ingestion

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

No additional information available

53 **Advice for firefighters**

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : NFPA Aerosol Level 1.

10/12/2014 EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

: Equip cleanup crew with proper protection. Avoid breathing dust, fume, gas, mist, vapor spray. Protective equipment

Emergency procedures : Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into

suitable containers.

: Store away from other materials. Methods for cleaning up

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Precautions for safe handling

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions. Do not handle until all safety precautions have been read and

understood. Eliminate all ignition sources if safe to do so. Do not breathe

dust,fumes,gas,mist,vapor spray.

Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after Hygiene measures

handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with

mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with

applicable regulations.

Storage conditions Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids. : Sources of ignition. Direct sunlight. Incompatible materials

Storage area : Store in a well-ventilated place.

Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

Control parameters

Petroleum Gases, Liquefied, Sweetened (68476-86-8)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Methyl Isobutyl Ketone (108-10-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	20 ppm

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m³)	97 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³

10/12/2014 EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Butoxyethanol (111-76-2)		
USA OSHA OSHA PEL (TWA) (ppm) 50 ppm		
USA OSHA OSHA PEL (TWA) (ppm) 50 ppm		

2-Aminoethanol (141-43-5)		
USA ACGIH	ACGIH TWA (ppm)	3 ppm
USA ACGIH	ACGIH STEL (ppm)	3 ppm

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to light yellow.

Odor : Mild . Alcohol odour. Ammonia odour.

Odor threshold : No data available

pH : 9

Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : -31.1 °C (Lowest Component-Propellant)

Flash point : -96.23 °C (Lowest Component-Propellant)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.98

Solubility : Soluble in water. Log Pow No data available Log Kow No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic Explosive properties No data available Oxidizing properties : No data available Explosive limits : No data available

10/12/2014 EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

VOC content : 9.8 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Acute toxicity	: Not classified
Methyl Isobutyl Ketone (108-10-1)	
LD50 oral rat	2080 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	>= 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	8.2- 16.4,Rat; Experimental value
LC50 inhalation rat (ppm)	2000 ppm/4h (Rat; Experimental value,Rat; Experimental value)
Ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
2-Butoxyethanol (111-76-2)	
LD50 oral rat	530 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 1746 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
Polyethylene Glycol 200-600 (25322-6	8-3)
LD50 oral rat	> 15000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
2-Aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Skin corrosion/irritation	: Not classified
	pH: 9
Serious eye damage/irritation	: Not classified
	pH: 9
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
•	

10/12/2014 EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)	
IARC group	1

2-Butoxyethanol (111-76-2)IARC group

IARC group 3

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause cancer by inhalation.

Symptoms/injuries after skin contact : May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin

rash/inflammation.

Symptoms/injuries after eye contact : May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye

tissue. Irritation of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Methyl Isobutyl Ketone (108-10-1)	
LC50 fish 1	505 mg/l (96 h; Pimephales promelas; GLP)
EC50 Daphnia 1	170 mg/l (48 h; Daphnia magna; Static system)
EC50 other aquatic organisms 1	400 mg/l (96 h; Selenastrum capricornutum; Growth rate)
LC50 fish 2	600 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	> 1000 mg/l (48 h; Daphnia magna; GLP)
Threshold limit algae 1	136 mg/l (Microcystis aeruginosa)
Threshold limit algae 2	725 mg/l (8 days: Scenedesmus guadricauda: Nominal concentration)

Ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)

2-Butoxyethanol (111-76-2)	
LC50 fish 1	116 ppm (96 h; Cyprinodon variegatus; Nominal concentration)
EC50 Daphnia 1	1700 mg/l (48 h; Daphnia sp.; Nominal concentration)
LC50 fish 2	1341 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	1720 mg/l (24 h; Daphnia magna)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	900 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	35 mg/l (192 h; Microcystis aeruginosa)

Polyethylene Glycol 200-600 (25322-68-3)	
LC50 fish 1	> 1000 mg/l (96 h; Pisces)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
LC50 fish 2	> 5000 mg/l (24 h; Carassius auratus)
Threshold limit other aquatic organisms 1	<= 100 mg/l (96 h; Plankton)
Threshold limit other aquatic organisms 2	> 1000 mg/l
Threshold limit algae 2	500 mg/l (720 h; Algae; No effect)

2-Aminoethanol (141-43-5)	
LC50 fish 1 150 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 1	140 mg/l (24 h; Daphnia magna)
LC50 fish 2 329.16 mg/l (96 h; Lepomis macrochirus)	
TLM fish 1	100 - 1000,96 h; Pisces

10/12/2014 EN (English US) 6/11

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday	, maior 20, 20, 27, maior and magazino	
2-Aminoethanol (141-43-5)	100 1000 0C h	
TLM other aquatic organisms 1 Threshold limit algae 1	100 - 1000,96 h	
Threshold limit algae 1 Threshold limit algae 2	0.97 mg/l (192 h; Scenedesmus quadricauda; Inhibitory)	
Threshold limit algae 2	35 mg/l (72 h; Algae)	
Methanol (67-56-1)		
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)	
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)	
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)	
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)	
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)	
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)	
12.2. Persistence and degradability		
MIGHTY GLASS CLEANER 18 OZ.		
Persistence and degradability	Not established.	
	AUTO 00 0\	
Petroleum Gases, Liquefied, Sweetened (6)	,	
Persistence and degradability	Not established.	
Methyl Isobutyl Ketone (108-10-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under	
2	anaerobic conditions. Low potential for adsorption in soil. Photolysis in the air.	
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance	
ThOD	2.72 g O ₂ /g substance	
BOD (% of ThOD)	0.76 % ThOD	
Ethanol (64-17-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O 2 /g substance	
Chemical oxygen demand (COD)	1.70 g O 2 /g substance	
ThOD	2.10 g O ₂ /g substance	
BOD (% of ThOD)	0.43 % ThOD	
2-Butoxyethanol (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O 2 /g substance	
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance	
ThOD	2.305 g O 2 /g substance	
BOD (% of ThOD)	0.31 % ThOD	
	O 0F9/ /4000 04 C\	
Persistence and degradability	Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
Fersisterice and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air.	
Dalam (hadana Ohara Loop 000 (05000 00 0)		
Polyethylene Glycol 200-600 (25322-68-3)	Diadogradohility in water no data available	
Persistence and degradability	Biodegradability in water: no data available.	
Nonyl Nonoxynol-5 (9014-93-1)		
Persistence and degradability	Not established.	
DI - Water (7789-20-0)		
Persistence and degradability	Not established.	
2-Aminoethanol (141-43-5)	Readily hindegradable in water Rindegradable in the soil	
Persistence and degradability Biochemical oxygen demand (BOD)	Readily biodegradable in water. Biodegradable in the soil.	
Chemical oxygen demand (COD)	0.80 g O 2 /g substance 1.34 g O 2 /g substance	
ThOD	2.49 g O 2 /g substance	
BOD (% of ThOD)	0.32 % ThOD	
	0.02 /0 IIIOD	
Proprietary Inhibitor Package (Proprietary)		
Persistence and degradability Not established.		
Methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	

10/12/2014 EN (English US) 7/11

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. //, No. 58 / Monday, N		
Methanol (67-56-1)		
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance	
ThOD	1.5 g O ₂ /g substance	
BOD (% of ThOD)	0.8 % ThOD	
12.3. Bioaccumulative potential		
MIGHTY GLASS CLEANER 18 OZ.		
Bioaccumulative potential	Not established.	
Petroleum Gases, Liquefied, Sweetened (6847	76 96 9/	
Bioaccumulative potential	Not established.	
	Not established.	
Methyl Isobutyl Ketone (108-10-1)		
BCF fish 1	2 - 5 (Pisces)	
Log Pow	1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Ethanol (64-17-5)		
BCF fish 1	1 (72 h; Cyprinus carpio)	
Log Pow	-0.31 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
2-Butoxyethanol (111-76-2)		
Log Pow	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
	, , ,	
Ammonium Hydroxide, Aqueous Solution, Co		
Bioaccumulative potential	Not bioaccumulative.	
Polyethylene Glycol 200-600 (25322-68-3)		
Log Pow	-1.2	
Bioaccumulative potential	Bioaccumulation: not applicable.	
Nonyl Nonoxynol-5 (9014-93-1)		
Bioaccumulative potential	Not established.	
·	THE COLUMNICATION.	
DI - Water (7789-20-0)		
Bioaccumulative potential	Not established.	
2-Aminoethanol (141-43-5)		
Log Pow	-1.91	
Bioaccumulative potential	Bioaccumulation: not applicable.	
Proprietary Inhibitor Package (Proprietary)		
Bioaccumulative potential	Not established.	
'	1101 000001010001	
Methanol (67-56-1)		
BCF fish 1	< 10 (72 h; Leuciscus idus)	
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)	
Log Pow	-0.77 (Experimental value; Other)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
12.4. Mobility in soil		
Methyl Isobutyl Ketone (108-10-1)		
Surface tension	0.024 N/m (20 °C)	
	0.02 : 1 viii (20 0)	
Ethanol (64-17-5)		
Surface tension	0.022 N/m (20 °C)	
2-Butoxyethanol (111-76-2)		
Surface tension	0.027 N/m (25 °C)	
2 Aminosthanol (4.44, 42.5)		
2-Aminoethanol (141-43-5)	0.050 N/m	
Surface tension	U.U3U IN/III	
Methanol (67-56-1)		
Surface tension	0.023 N/m (20 °C)	

10/12/2014 EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste

disposal facility, in accordance with local, regional, national, international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.2, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.2, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.2, Limited Quantity

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

non-flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard

Classes

: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

MIGHTY GLASS CLEANER 18 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
	Immediate (acute) health hazard
	Sudden release of pressure hazard

Petroleum Gases, Liqueriea, Sweetenea (68476-86-8)		0-80-8)
	SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
		Fire hazard
		Sudden release of pressure hazard

2-Aminoethanol (141-43-5)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

10/12/2014 EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

15.2. International regulations

CANADA

MIGHTY GLASS CLEANER 18 OZ.	
WHMIS Classification	Class A - Compressed Gas
Methanol (67-56-1)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45 Muta.Cat.2; R46 F+; R12 Xn; R20/21/22 Xn; R68/20/21/22

Full text of R-phrases: see section 16

15.2.2. National regulations

No additional information available

15.3. US State regulations

2-Butoxyethanol (111-76-2)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute toxicity (dermal) Category 3
Acute toxicity (inhalation:dust,mist) Category 3
Acute toxicity (inhalation:gas) Category 3
Acute toxicity (oral) Category 3
Acute toxicity (dermal) Category 4
Acute toxicity (inhalation:dust,mist) Category 4
Acute toxicity (oral) Category 4
Hazardous to the aquatic environment - Acute Hazard Category 1
Carcinogenicity Category 1A
Gases under pressure Compressed gas
Serious eye damage/eye irritation Category 2A
Flammable gases Category 1
Flammable liquids Category 1
Flammable liquids Category 2
Flammable liquids Category 4
Germ cell mutagenicity Category 1B
Skin corrosion/irritation Category 1A
Skin corrosion/irritation Category 1B
Skin corrosion/irritation Category 2

10/12/2014 EN (English US) 10/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H370	Causes damage to organs
H400	Very toxic to aquatic life


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

10/12/2014 EN (English US) 11/11