Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 08/28/2014 :

Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking         1.1.       Product identifier         Product form       : Mixture         Trade name       : MIGHTY NON-CHLORINATED BRAKE CLEANER 14 OZ.         Product code       : BK150         1.2.       Relevant identified uses of the substance or mixture and uses advised against         Use of the substance/mixture       : Brake Part Cleaner         1.3.       Details of the supplier of the safety data sheet         Mighty Auto Parts       650 Engineering Drive         Norcross, Georgia 30092       T770-448-3900         1.4.       Emergency telephone number         Emergency number       : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)         SECTION 2: Hazards identification       21.         21.       Classification of the substance or mixture         Classification of the substance or mixture       Classification of the substance or mixture         Classification of the substance or mixture       Stin Irrit. 2         Classification of 1 H222       Compressed gas H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT R E 2       H373         Full text of H-phrases: see section 16
Product form       : Mixture         Trade name       : MIGHTY NON-CHLORINATED BRAKE CLEANER 14 OZ.         Product code       : BK150 <b>1.2.</b> Relevant identified uses of the substance or mixture and uses advised against         Use of the substance/mixture       : Brake Part Cleaner <b>1.3.</b> Details of the supplier of the safety data sheet         Mighty Auto Parts         650 Engineering Drive         Norcross, Georgia 30092         T770-448-3900 <b>1.4.</b> Emergency telephone number         Emergency telephone number         Emergency telephone number         Emergency telephone number <b>2.1.</b> Classification of the substance or mixture <b>Classification (GHS-US)</b> Flam. Aerosol 1 H222         Compressed gas H280         Skin Irrit. 2 H315         Repr. 2 H361         STOT RE 2 H373
Trade name: MIGHTY NON-CHLORINATED BRAKE CLEANER 14 OZ.Product code: BK150I.2. Relevant identified uses of the substance or mixture and uses advised againstUse of the substance/mixture: Brake Part CleanerI.3. Details of the supplier of the safety data sheetMighty Auto Parts S50 Engineering Drive Norcross, Georgia 300921.4. Emergency telephone numberEmergency number: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)SECTION 2: Hazards identification2.1. Classification of the substance or mixtureCompressed gas H280 Skin Irrit. 2Skin Irrit. 2Skin Irrit. 2H336 STOT RE 2STOT RE 2H336 STOT RE 2
Product code       : BK150         1.2.       Relevant identified uses of the substance or mixture and uses advised against         Use of the substance/mixture       : Brake Part Cleaner         1.3.       Details of the supplier of the safety data sheet         Mighty Auto Parts 650 Engineering Drive Norcross, Georgia 30092 T 770-448-3900       Socration (Secondary Secondary Second
1.2. Relevant identified uses of the substance or mixture and uses advised against         Use of the substance/mixture       : Brake Part Cleaner         1.3. Details of the supplier of the safety data sheet         Mighty Auto Parts         650 Engineering Drive         Norcross, Georgia 30092         T 770-448-3900         1.4. Emergency telephone number         Emergency number       : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)         SECTION 2: Hazards identification         2.1. Classification of the substance or mixture         Classification (GHS-US)         Flam. Aerosol 1         Flam. Aerosol 1         H222         Compressed gas H280         Skin Irrit. 2       H315         Repr. 2       H386         STOT RE 2       H373
Use of the substance/mixture : Brake Part Cleaner 1.3. Details of the supplier of the safety data sheet Mighty Auto Parts 650 Engineering Drive Norcross, Georgia 30092 T 770-448-3900 1.4. Emergency telephone number Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International) SECTION 2: Hazards identification SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification (GHS-US) Flam. Aerosol 1 H222 Compressed gas H280 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT SE 3 H336
1.3. Details of the supplier of the safety data sheet         Mighty Auto Parts         650 Engineering Drive         Norcross, Georgia 30092         T 770-448-3900         1.4. Emergency telephone number         Emergency number       : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)         SECTION 2: Hazards identification         2.1. Classification of the substance or mixture         Classification (GHS-US)         Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
Mighty Auto Parts         650 Engineering Drive         Norcross, Georgia 30092         T 770-448-3900         1.4. Emergency telephone number         Emergency number       : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)         SECTION 2: Hazards identification         2.1. Classification of the substance or mixture         Classification (GHS-US)         Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
650 Engineering Drive Norcross, Georgia 30092 T 770-448-3900 1.4. Emergency telephone number Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International) SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification (GHS-US) Flam. Aerosol 1 H222 Compressed gas H280 Skin Irit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373
Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International) SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification (GHS-US) Flam. Aerosol 1 H222 Compressed gas H280 Skin Irrit. 2 H315 Repr. 2 H361 STOT SE 3 H336 STOT RE 2 H373
SECTION 2: Hazards identification         2.1.       Classification of the substance or mixture         Classification (GHS-US)         Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
2.1.       Classification of the substance or mixture         Classification (GHS-US)         Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
Classification (GHS-US)         Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
Flam. Aerosol 1       H222         Compressed gas       H280         Skin Irrit. 2       H315         Repr. 2       H361         STOT SE 3       H336         STOT RE 2       H373
2.2. Label elements
GHS-US labeling
Hazard pictograms (GHS-US) : GHS02 GHS04 GHS07 GHS08
Signal word (GHS-US) : Danger
Hazard statements (GHS-US)       : H222 - Extremely flammable aerosol         H280 - Contains gas under pressure; may explode if heated         H315 - Causes skin irritation         H336 - May cause drowsiness or dizziness         H361 - Suspected of damaging fertility or the unborn child         H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (GHS-US)       : P201 - Obtain special instructions         P202 - Do not handle until all safety precautions have been read and understood         P210 - Keep away from heat,sparks,open flames,hot surfaces No smoking         P211 - Do not spray on an open flame or other ignition source         P251 - Pressurized container: Do not pierce or burn, even after use         P260 - Do not breathe dust,fumes,gas,mist,vapor spray         P261 - Avoid breathing dust,fume,gas,mist,vapor spray         P262 - Use only outdoors or in a well-ventilated area         P280 - Wear protective gloves,protective clothing,eye protection,face protection         P302+P352 - If on skin: Wash with plenty of soap and water         P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing         P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.         P314 - Get medical advice/attention if you feel unwell.         P312 - Specific treatment: See section 4.1 on SDS         P332+P313 - If skin irritation occurs: Get medical advice/attention         P32+P333 - Store in a well-ventilated place. Keep container tightly closed         P403 - P233 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place           10/12/2014         EN (English US)         1/2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with
local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards not contributing to the

: Contains gas under pressure; may explode if heated.

classification 2.4. Unknown ad

2.4. Unknown acute toxicity (GHS-US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Heptane, Branched Cyclic	(CAS No) 426260-76-6	59.52 - 62	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Toluene	(CAS No) 108-88-3	30 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Heptane	(CAS No) 142-82-5	15.5 - 27.9	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	1 - 5	Compressed gas, H280

SECTION 4: First aid measures				
4.1. Description of first aid measure	S			
First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medica advice/attention.			
First-aid measures after inhalation	: Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.			
First-aid measures after skin contact	<ul> <li>Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs Get medical advice/attention.</li> </ul>			
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.			
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.			
4.2. Most important symptoms and effects, both acute and delayed				
Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs.			
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.			
Symptoms/injuries after skin contact	: Causes skin irritation.			
Symptoms/injuries after eye contact	: Causes eye irritation.			
4.3. Indication of any immediate medical attention and special treatment needed				
No additional information available				
<b>SECTION 5: Firefighting measure</b>	es			
5.1. Extinguishing media				
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.			
Unsuitable extinguishing media	: Do not use a heavy water stream.			
5.2. Special hazards arising from th	e substance or mixture			
Fire hazard	: Extremely flammable aerosol.			

Explosion hazard		. Extremely hammable derosol.
		: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
5.3.	Advice for firefighters	
Firefigh	ting instructions	<ul> <li>Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.</li> </ul>

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting Other information	<ul><li>Do not enter fire area without proper protective equipment, including respiratory protection.</li><li>Aerosol level 3.</li></ul>
SECTION 6: Accidental release n	neasures
6.1. Personal precautions, protectiv	e equipment and emergency procedures
General measures	: No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.
6.1.1. For non-emergency personnel	
Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	Notify authorities if liquid enters sewers or public waters.
6.3. Methods and material for conta	inment and cleaning up
For containment	: Dam up the liquid spill.
Methods for cleaning up	: Store away from other materials.
6.4. Reference to other sections	
See Heading 8. Exposure controls and pers	onal protection.
<b>SECTION 7: Handling and storag</b>	e
7.1. Precautions for safe handling	
Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or bur even after use.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Wash affected areas thoroughly after handling.
7.2. Conditions for safe storage, inc	luding any incompatibilities
Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage area	: Store in a well-ventilated place.
7.3. Specific end use(s)	
Follow Label Directions.	

### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

Toluene (108-88-3)				
USA ACGIH	ACGIH TWA (mg/m³)	75 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	20 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm		
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm		
Heptane (142-82-5)				
USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	400 ppm		
Heptane, Branched Cyclic (4				
USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	500 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm		

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>	
USA ACGIH	ACGIH TWA (ppm)	5000 ppm	
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	54000	
USA ACGIH	ACGIH STEL (ppm)	30000 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>	
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm	

#### 8.2. **Exposure controls** Appropriate engineering controls

Personal protective equipment

: Local exhaust venilation, vent hoods.

: Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.

<b>SECTION 9: Physical and chemical p</b>	properties			
9.1. Information on basic physical and chemical properties				
Physical state	: Gas			
Appearance	: Liquid.			
Color	: Colourless to light yellow.			
Odor	: Solvent-like odour. Strong odour.			
Odor threshold	: No data available			
рН	: No data available			
Relative evaporation rate (butyl acetate=1)	: No data available			
Melting point	: No data available			
Freezing point	: No data available			
Boiling point	: 88 °C (Lowest Component)			
Flash point	: -9 °C (Lowest Component)			
Auto-ignition temperature	: No data available			
Decomposition temperature	: No data available			
Flammability (solid, gas)	: No data available			
Vapor pressure	: No data available			
Relative vapor density at 20 °C	: No data available			
Relative density	: 0.75			
Solubility	: Poorly soluble in water.			
Log Pow	: No data available			
Log Kow	: No data available			
Viscosity, kinematic	: No data available			
Viscosity, dynamic	: No data available			
Explosive properties	: No data available			
Oxidizing properties	: No data available			
Explosive limits	: No data available			
9.2. Other information				
VOC content	: 95.5 %			
<b>SECTION 10: Stability and reactivity</b>				

#### 10.1. Reactivity

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

sources of ignition.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Direct sunlight. Extremely high or low temperature	es. Heat. Sparks. Open flame. Overheating.
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
Toxic fume Carbon monoxide. Carbon dioxide.	
SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
Heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Heptane, Branched Cyclic (426260-76-6)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Toluene (108-88-3)	
IARC group	3
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.

SECTION 12: Ecological information				
12.1.	Toxicity			

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3	
Toluene (108-88-3)	
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)
Heptane (142-82-5)	
LC50 fish 1	375 mg/l (96 h; Tilapia mosambica; Nominal concentration)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
EC50 Daphnia 1	1.5 mg/l (48 h; Daphnia magna)
LC50 fish 2	<ul> <li>&gt; 100 mg/l (96 h; Oncorhynchus kisutch)</li> </ul>
TLM fish 1	4924 mg/l (48 h; Gambusia affinis)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit algae 1	<ul> <li>&gt; 200 mg/l (Scenedesmus quadricauda; Toxicity test)</li> </ul>
Threshold limit algae 2	1.5 mg/l (8 h; Algae; Photosynthesis)
Carbon Dioxide, Liquefied, Under Pressure	
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)
2.2. Persistence and degradability	
MIGHTY NON-CHLORINATED BRAKE CLE	ANER 14 OZ.
Persistence and degradability	Not established.
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O 2 /g substance
Chemical oxygen demand (COD)	2.52 g O 2 /g substance
ThOD	3.13 g O 2 /g substance
BOD (% of ThOD)	0.69 % ThOD
Heptane (142-82-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	1.92 g O 2 /g substance
Chemical oxygen demand (COD)	0.06 g O 2 /g substance
ThOD	3.52 g O 2 /g substance
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5
Heptane, Branched Cyclic (426260-76-6)	
Persistence and degradability	May cause long-term adverse effects in the environment.
<u> </u>	
Carbon Dioxide, Liquefied, Under Pressure	
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
2.3. Bioaccumulative potential	
MIGHTY NON-CHLORINATED BRAKE CLE	ANER 14 OZ.
Bioaccumulative potential	Not established.
·	
Toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
BCF fish 2	90 (72 h; Leuciscus idus)
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Heptane (142-82-5)	
Heptane (142-82-5) BCF other aquatic organisms 1	552
	552 4.66 (Experimental value; 4.5; Literature)
BCF other aquatic organisms 1	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, Branched Cyclic (426260-76-6)	
Bioaccumulative potential	Not established.
Carbon Dioxide, Liquefied, Under Pressure	(124-38-9)
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.
12.4. Mobility in soil	
Toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
Heptane (142-82-5)	
Surface tension	0.020 N/m (20 °C)
12.5. Other adverse effects	
Other information	: Avoid release to the environment.
SECTION 13: Disposal consideration	ns
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / A	
US DOT (ground): UN1950, Aerosols, 2.1	I, Limited Quantity
ICAO/IATA (air): UN1950, Aerosols, 2.1	I, Limited Quantity
IMO/IMDG (water): UN1950, Aerosols, 2.1	I, Limited Quantity
Special Provisions: N82 - See 173.306 of	this subchapter for classification criteria for flammable aerosols.
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Aerosols
	flammable, (each not exceeding 1 L capacity)
Department of Transportation (DOT) Hazard Classes	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport No additional information available	
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
DOT Vessel Stowage Other	<ul> <li>passenger vessel.</li> <li>48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials</li> </ul>
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	
10/12/2014	EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information	
15.1. US Federal regulations	
MIGHTY NON-CHLORINATED BRAKE CLEAN	ER 14 OZ.
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard Immediate (acute) health hazard Sudden release of pressure hazard
Toluene (108-88-3)	
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substar	nces Control Act) inventory
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
Heptane, Branched Cyclic (426260-76-6)	
Not listed on the United States TSCA (Toxic Subs	stances Control Act) inventory
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

#### 15.2. International regulations

#### CANADA

MIGHTY NON-CHLORINATED BRAKE CLEANER 14 OZ.	
WHMIS Classification	Class B Division 5 - Flammable Aerosol
Toluene (108-88-3)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Heptane, Branched Cyclic (426260-76-6)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

#### **EU-Regulations**

 Toluene (108-88-3)

 Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63 F; R11 Xn; R48/20 Xi; R38 Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

15.3. US State regulations	
MIGHTY NON-CHLORINATED BRAKE CLEANER	14 OZ.
State or local regulations	U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
Toluene (108-88-3)	
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Catego
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Catego
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
	exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: B

**Personal Protection** 

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.